




500Vdc Isolation Single & Dual Output 1.8 Watt Dc-Dc Converter



FEATURES:

- 24PIN DIP Package
- High Efficiency up to 85%
- Recognized By UL 60950-1
- Unregulated & Regulated Output Types
- Low Ripple & Noise
- Internal SMD Construction
- Industry Standard Pinout
- Operating Temperature: -40°C TO +85°C
- No External Component Required



Specifications typical at TA=25°C, nominal input voltage and rated output current unless otherwise specified

Part Number	Output Voltage	Output Current	Efficiency
	Vdc	mA	%TYP
40D-XXS05RNL	5	360	58
40D-XXS05NNL	5	360	70
40D-XXD05NNL	±5	±180	70
40D-XXS09RNL	9	200	60
40D-XXS09NNL	9	200	70
40D-XXD09NNL	±9	±100	70
40D-XXS12RNL	12	150	60
40D-XXS12NNL	12	150	75
40D-XXD12RNL	±12	±75	60
40D-XXD12NNL	±12	±75	75
40D-XXS15RNL	15	120	60
40D-XXS15NNL	15	120	75
40D-XXD15RNL	±15	±60	60
40D-XXD15NNL	±15	±60	75
40D-XXS24RNL	24	75	60
40D-XXS24NNL	24	75	80
40D-XXD24RNL	±24	±38	60
40D-XXD24NNL	±24	±38	80

Note:1."XX" Is Input Voltage :05=5Vdc,09=9Vdc,12=12Vdc,15=15Vdc,24=24Vdc.

2.The input voltage increases, there will be an increase in efficiency.

Input Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Tolerance	Vo,lo Nom			±10	%
Filter	Capacitor				

Output Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Tolerance	100% full load			±5	%
Short Circuit Protection	Regulated(Continuous)				
Short Circuit Protection	Unregulated(Short Trem)			1Sec	
Line Regulation	Regulated			±0.3	%
Load Regulation	Regulated			±0.5	%
Ripple & Noise	BW=DC To 20MHz			50	mVp-p
Line Regulation	Unregulated (For 1% of Vin)		1.2		%
Load Regulation	Unregulated (20% To 100% F.L)			10	%

General Specifications

Parameters	Conditions	Min	Typ	Max	Units
Isolation Resistance	500Vdc	1000			MΩ
Switching Frequency	Full load,nominal input		50		KHz
Operating Temperature		-40		85	°C
Humidity	Non Condensing			95	%
Cooling	Free air Convection				
Case material	DAP				
MTBF	MIL-HDBK-217F@25°C(Unregulated)	2500000			Hours
MTBF	MIL-HDBK-217F@25°C(Regulated)	1500000			Hours
Weight			9.0		g
Dimensions			33.02X14.73X10.41		mm



500Vdc Isolation Single & Dual Output 1.8 Watt Dc-Dc Converter

Temperature Derating Graph

Output Power (%) vs Ambient Temperature (°C)

Recommended Test Circuit

Single Output Test Circuit

5V :Cin 4.7uF,25V 5V :Cout 4.7uF,25V
 9V :Cin 4.7uF,25V 9V :Cout 2.2uF,25V
 12V:Cin 2.2uF,25V 12V:Cout 1uF,25V
 15V:Cin 2.2uF,25V 15V:Cout 0.47uF,50V
 24V:Cin 1uF,50V 24V:Cout 0.47uF,50V

Dual Output Test Circuit

5V :Cin 4.7uF,25V 5V :Cout 4.7uF,25V -Vout
 9V :Cin 4.7uF,25V 9V :Cout 2.2uF,25V
 12V:Cin 2.2uF,25V 12V:Cout 1uF,25V
 15V:Cin 2.2uF,25V 15V:Cout 0.47uF,50V
 24V:Cin 1uF,50V 24V:Cout 0.47uF,50V

Tolerance Envelope Graph

UNREGULATED

Output Voltage (%) vs Output Current (%)

Part Number

40D - 05 S 05 R NL

A B C D E F

A:Series
 B:Input Voltage
 C:Single(S)Dual(D)
 D:Output Voltage
 E:Regulated(R)Unregulated(N)
 F:RoHS Version

Markings and dimensions

Packaging

Size(mm)		
A	B	C
13.23	12.30	530

UNIT: mm Unless otherwise specified, all tolerances are ±0.25

PIN Connection

PIN	1,24	2	3	10	11,14	12,13	15	22	23	Other
Single	+Vin	NC	NC	-Vout	+Vout	-Vin	-Vout	NC	NC	NC
Dual	+Vin	-Vout	Com	Com	+Vout	-Vin	Com	Com	-Vout	NC